

1114002  
1174003

THE DRYWALL LIFTER

# PANELLIFT®

PATENT NO.  
3,828,942

MADE IN U.S.A. BY **Telpro Inc.**

## MODEL 138-2 OPERATOR'S MANUAL

Read and become familiar with this manual BEFORE operating unit.

### ⚠ Warning ⚠

Read and follow these warnings and the instructions that follow. Failure to do so could result in serious property damage, serious bodily injury, and/or death:

• **BEFORE** operating this equipment, thoroughly read this set of instructions, make sure you understand them, and only then follow the step-by-step directions. **FAILURE TO READ AND FOLLOW THESE INSTRUCTIONS** could result in failure of the equipment. Failure of the equipment while the lift is raised can include a sudden and rapid lowering of the lift and load possibly resulting in serious property damage, serious bodily injury and/or death.

• Use and maintenance of the PANELLIFT® shall be limited to authorized personnel who are trained in the proper techniques for its safe operation and maintenance and who are familiar with the various hazards of overhead material handling.

• As with any lifting equipment, **ALWAYS WEAR A HARD HAT** when operating the PANELLIFT®. Failure to do so could result in serious bodily injury and/or death.

• **DO NOT ATTEMPT TO USE YOUR PANELLIFT® IF ANY PART IS MISSING, DAMAGED OR WORN. ORDER A REPLACEMENT PART IMMEDIATELY.** Using a PANELLIFT® with missing, damaged or worn components can result in failure of the unit and possibly serious property damage, serious bodily injury, and/or death.

• **DO NOT** pass your hand through the spokes on the winch when operating the unit as this could result in serious bodily injury.

• **INSPECT THE CABLE BEFORE EACH USE. REPLACE AT THE FIRST SIGN OF WEAR.** A worn, damaged or improperly installed cable can fail resulting in a sudden and rapid lowering of the lift and the load and possibly resulting in serious property damage, serious bodily injury, and/or death. Inspect the cable by disassembling the telescoping system as shown in steps 1-4 on page 9 of this manual and examine the full length of the cable for signs of damage or wear. (See page 16 for general standards for cable inspection.)

• **The weight capacity of the PANELLIFT® wallboard lift is 150 lbs. (68 kg). DO NOT load the unit beyond this limit. Load only one sheet of wallboard at a time.** Failure to follow this warning can result in damage to the PANELLIFT® contributing to a sudden failure of the machine and serious property damage, serious bodily injury, and/or death.

• The PANELLIFT® is designed exclusively as a wallboard lift and shall be used for no other purpose. The PANELLIFT® is not a personnel lift or platform and shall not be used as such. Using the PANELLIFT® for purposes other than a wallboard lift can subject the unit to stresses and loads that it was not designed to carry. This can result in failure of the unit which may include a sudden and rapid lowering of the lift and the load possibly resulting in serious property damage, serious bodily injury and/or death.

• The PANELLIFT® is made of steel which conducts electricity. **KEEP THE UNIT AWAY FROM LIVE ELECTRICAL WIRES.** Failure to do so could result in electrocution.

• Use only factory authorized replacement parts. Installation of other parts can compromise the safe design of the PANELLIFT® and may cause failure of the unit possibly resulting in serious property damage, serious bodily injury, and/or death.

**??Questions??** - Call Telpro Inc. Customer Service at 1-800-448-0822 or 701-775-0551


# CONTENTS

---

Assembly . . . . .	Page 1
Operation . . . . .	Page 3
Disassembly . . . . .	Page 4
Installation of Extension 186-00 . . . . .	Page 6
Cable Replacement . . . . .	Page 7
Parts Index . . . . .	Page 17
Recommendations and Special Information . . . . .	Page 19


---

## USER COMPONENTS




1. Complete frame assembly with winch and standard telescoping sections
2. Cradle assembly - less detachable cross arms
3. Cradle cross arms
4. Complete tripod base assembly


# ASSEMBLY




1. Begin by setting up the tripod base: press down on the slide yoke ring and swing the outer legs out until they lock in the working position (note the holes on the bottom of the slide tube).




2C. To hold the tripod base in position during this procedure set the backstop as shown.




2A. Place the frame assembly on the tripod base.




2D. When the frame is correctly positioned on the tripod base release the backstop.




2B. Pocket "A" slides OVER angle "B" while angle "C" slides INSIDE angle "D".




3. To move the winch into the working position rotate the winch forward slightly with your right hand while raising the brake arm with your left hand.




4. Raise the brake arm all the way up, grasp the winch post, and squeeze the brake arm firmly as shown.




5. Place your right hand on top of the frame and pull the winch assembly towards you. While pulling the winch towards you, grip the brake arm sufficiently to prevent back-lash of the cable on the winch.




6. When the winch is fully extended, release the brake arm and swing the retaining hook away from the telescoping sections.




7. Now push the winch assembly back towards the frame. This action will automatically engage the slide bar lock. ALWAYS check to make sure that the slide bar lock is fully engaged by rotating it clockwise as far as possible before proceeding. The illustration shows a fully engaged slide bar lock. NOTE: DO NOT tighten the slide bar lock nut assembly. This will make it impossible to collapse the PANELLIFT® properly for transport and storage.



8. Mount the cradle on top of the telescoping section. Flip out the tilt latch to allow the cradle to tilt for loading and for hanging dry-wall on sidewalls and sloped ceilings.




9. Place the tapered plates of the crossarms into the tapered sockets on the cradle. The spring tab on the back of the crossarm will lock it into place.





10. To extend the outriggers for use, pull out on the outrigger lock pin with your right hand and slide the outrigger out with your left hand as shown. The lock pin will engage at three different points on the outrigger: fully retracted, extended 21", or extended 33". MAKE SURE that the lock pins are engaged in one of these three positions before loading the unit. DO NOT use the PANELLIFT® with the outriggers extended beyond the 33" point. Retract the outriggers when storing or transporting the unit.


# OPERATION




1. To Load: Set the backstop on the tripod base to hold the unit in position. Extend the cradle outriggers to properly support the drywall, tilt the cradle, and swing out the cross arm support hooks. Load the PANELLIFT® Drywall Lift from the front as shown with the face paper of the drywall contacting the cradle.



2. To raise the PANELLIFT® Drywall Lift rotate the winch wheel in the direction shown. The brake arm is spring loaded to hold the winch automatically at any height.




3. To lower the PANELLIFT® Drywall Lift control the backward rotation of the winch by grasping the winch handle with your right hand BEFORE releasing the brake with your left hand. ALWAYS use this two hand method when lowering the PANELLIFT® Drywall Lift.



4. The PANELLIFT® Drywall Lift will hold drywall in position on sidewalls and sloped ceilings in addition to level ceilings. The cradle also tilts up to 10° longitudinally. USE THE BACKSTOP ON THE TRIPOD BASE WHEN WORKING ON SIDEWALLS AND SLOPED CEILINGS.


# DISASSEMBLY

The PANELLIFT® should be disassembled as follows for transport and compact storage:




1. Slide the cradle outriggers all the way in.


2. Remove the cross arms by pressing the spring tab on the bottom and sliding the cross arm out of the tapered socket.




3. Lock the cradle tilt latch and lift the cradle off of the frame.




4. Rotate the winch forward one full rotation.




5. Raise up on the slide bar with your left hand while rotating the slide bar lock counter-clockwise with your right hand.



6. While holding the slide bar lock in this disengaged position with your right hand, push down on top of the telescoping section with your left hand. This action will cause the winch assembly to move toward the frame.




7. With the telescoping section all the way down, position the retaining hook over the top as shown.



8. Hold the retaining hook in this position with your left hand and rotate the winch forward with your right hand. This will cause the winch assembly to fold up against the frame. When the slide bar contacts the frame, tighten the cable just sufficiently to hold the winch in the collapsed position.




9. Lift the frame off of the tripod base.




10. To collapse the tripod base, press down on the slide yoke ring and swing the legs in until they lock in the closed position.

## INSTALLATION OF EXTENSION 186-00




The extension 186-00 consists of two 6' telescoping sections and allows the PANELLIFT® Drywall Lift to reach 15 feet. This unit easily interchanges with the standard 4' telescoping sections shown here for comparison.

# INSTALLATION OF EXTENSION 186-00




1. Loosen the cable from the mooring tab on the winch and pull it out through the winch drum.



2. Pinch the two telescoping sections together and lift them out as a unit. Pulling the cable will help to raise them.




3. Remove the two telescoping sections completely from the frame housing. Pull the cable out with them.



4. Feed the crimped end of the 186-00 cable through the frame sheave pocket from the top. It is VERY IMPORTANT that the cable passes OVER THE TOP of the brass sheave as shown here.



5. Pull the slack cable through the sheave pocket and slide the telescoping sections into the frame housing.



6. Feed the cable through the winch drum and secure it firmly behind the mooring tab as shown. Rotate the winch wheel in the direction indicated to take up the slack in the cable.

## ⚠Warning⚠

Read and follow these warnings and the instructions that follow. Failure to do so could result in serious property damage, serious bodily injury, and/or death:

• **BEFORE** attempting to replace the cable, thoroughly read this set of instructions, make sure you understand them, and only then follow the step-by-step directions. **FAILURE TO READ AND FOLLOW THESE INSTRUCTIONS** could result in an incorrectly installed cable which may detach or fail. Failure of the cable while the lift is raised will result in a sudden and rapid lowering of the lift and load possibly resulting in serious property damage, serious bodily injury and/or death.

• **Read** and become familiar with the complete Operator's Manual before operating the PANELLIFT® drywall lift.

• Use and maintenance of the PANELLIFT® shall be limited to authorized personnel who are trained in the proper techniques for its safe operation and maintenance and who are familiar with the various hazards of overhead material handling.

• As with any lifting equipment, **ALWAYS WEAR A HARD HAT** when operating the PANELLIFT®. Failure to do so could result in serious bodily injury and/or death.

• **DO NOT ATTEMPT TO USE YOUR PANELLIFT® IF ANY PART IS MISSING, DAMAGED OR WORN. ORDER A REPLACEMENT PART IMMEDIATELY.** Using a PANELLIFT® with missing, damaged or worn components can result in failure of the unit and possibly serious property damage, serious bodily injury, and/or death.

• **DO NOT** pass your hand through the spokes on the winch when operating the unit as this could result in serious bodily injury.

• **INSPECT THE CABLE BEFORE EACH USE. REPLACE AT THE FIRST SIGN OF WEAR.** A worn, damaged or improperly installed cable can fail resulting in a sudden and rapid lowering of the lift and the load and possibly resulting in serious property damage, serious bodily injury, and/or death. Inspect the cable by disassembling the telescoping system as shown in steps 1-4 on page 9 of this manual and examine the full length of the cable for signs of damage or wear. (*See page 16 for general standards for cable inspection.*)



• **The weight capacity of the PANELLIFT® wallboard lift is 150 lbs. (68 kg). DO NOT load the unit beyond this limit. Load only one sheet of wallboard at a time.** Failure to follow this warning can result in damage to the PANELLIFT® contributing to a sudden failure of the machine and serious property damage, serious bodily injury, and/or death.

• The PANELLIFT® is designed exclusively as a wallboard lift and shall be used for no other purpose. The PANELLIFT® is not a personnel lift or platform and shall not be used as such. Using the PANELLIFT® for purposes other than a wallboard lift can subject the unit to stresses and loads that it was not designed to carry. This can result in failure of the unit which may include a sudden and rapid lowering of the lift and the load possibly resulting in serious property damage, serious bodily injury and/or death.

• The PANELLIFT® is made of steel which conducts electricity. **KEEP THE UNIT AWAY FROM LIVE ELECTRICAL WIRES.** Failure to do so could result in electrocution.

• Use only factory authorized replacement parts. Installation of other parts can compromise the safe design of the PANELLIFT® and may cause failure of the unit possibly resulting in serious property damage, serious bodily injury, and/or death.

# Terms used in this section of the manual:



## Symbols used in this manual:




This symbol is used to alert the user to important operating and/or maintenance instructions which if not heeded may result in serious property damage, serious bodily injury and/or death.




This symbol is used to help illustrate and clarify specific information that is referred to in the text.



This symbol is used to help illustrate the path of travel that the cable takes through the telescoping system when a view of that path of travel is obstructed by a component of the telescoping system itself.



??Questions?? - Call Telpro Inc. Customer Service at 1-800-448-0822 or 701-775-0551




1. Loosen the cable from the mooring tab on the winch and pull it out from the winch drum. **BE CAREFUL!** A worn cable can have frayed strands. Wearing gloves will help protect your hands.



2. Pinch the two telescoping sections together and lift them out as a unit. Pulling on the cable will help to raise them.




3. Remove the two telescoping sections completely from the frame housing. Pull the cable completely out from the frame along with them. **BE CAREFUL** for loose strands or frays on the cable.




4. Pull the "A" section out of the "B" section. If you are working with an extension 186-00, you will pull the "E" section out of the "F" section.

5. Remove the old cable from the "A" and "B" sections. **WARNING!! Destroy and discard the old cable along with any anchoring devices used to hold it in place to prevent accidental reuse which could result in failure of the cable.** Failure of the cable while the lift is raised will result in a sudden and rapid lowering of the lift and load which could result in serious property damage, serious bodily injury, and/or death.




**Note:** If you are removing an older style of cable, you will need to use a hammer and tapered punch to loosen the anchoring wedge as shown in the two photos above. If you are replacing a newer cable (like the one you are installing) simply pull the cable completely out of both telescoping sections in the direction shown below. **Make sure to destroy and discard the old cable.**




**Pull cable out to remove**


**??Questions??** - Call Telpro Inc. Customer Service at 1-800-448-0822 or 701-775-0551



6. Make sure the rubber sleeve is seated completely against the anchoring bushing in the new cable.




7. Feed the copper crimped end of the cable through the "A" section anchoring "V" from the bottom as shown.




8. Pull the cable all the way through until the rubber sleeve passes under the anchoring "V" and the anchoring bushing sits tightly against the "V". **WARNING!! DO NOT use a hammer to pound this assembly in place and DO NOT use a wedge or any other anchoring device.** Doing so may damage the steel ball crimp and may cause the cable to fail under a load, possibly resulting in serious property damage, serious bodily injury, and/or death.

## ⚠ WARNING ⚠

The cable **MUST** feed in from the bottom of the "A" exactly as shown in steps 7 and 8 in order to function properly. Failure to install the cable correctly as shown can cause wear-ing of the cable for which it is not designed which can result in failure of the cable. Failure of the cable while the lift is raised will result in a sudden and rapid lowering of the lift and the load possibly resulting in serious property damage, serious bodily injury, and/or death.




**DO NOT** feed the cable into the "A" section as shown above!!




9. Load the cable installation tool as shown. To ease the installation procedure, there should not be more than 1" of cable extending at the end.


**??Questions??** - Call Telpro Inc. Customer Service at 1-800-448-0822 or 701-775-0551




10. Use the special tool provided to insert the copper crimped end of the cable into the **TOP** end of the "B" section as shown in this cut away view. If your "B" section is the factory original and not a replacement, the top is the painted end and the bottom has several inches of unfinished surface. If both ends of your "B" section are painted it is either a replacement or you are working on the "F" section of an extension 186-00. In either of these cases wear marks on the section should give you an indication of which end is the top.



11. Insert the crimped end of the cable up into the bottom of the sheave pocket at the end nearest the end of the "B" section as shown.




12. With a motion like that of tightening a screw driver, twist the cable installation tool while holding the crimped end of the cable up into the sheave pocket. The cable will pop loose from the tool and pop up through the sheave pocket as shown in this cut away view.



13. Pull the copper crimped end of the cable out through the sheave pocket in the direction shown.


## ⚠ WARNING ⚠

The cable **MUST** feed in from the top of the "B" exactly as shown in steps 10 - 13 in order to function properly. Failure to install the cable correctly as shown can cause wearing of the cable for which it is not designed which can result in failure of the cable. Failure of the cable while the lift is raised will result in a sudden and rapid lowering of the lift and the load possibly resulting in serious property damage, serious bodily injury, and/or death.




14. Feed the crimped end of the cable down into the slot (a) of the "B" section and out the bottom end of the telescoping section (b) as shown. Pull the cable completely through to remove the slack.


**??Questions??** - Call Telpro Inc. Customer Service at 1-800-448-0822 or 701-775-0551



15. Re-load the copper crimped end of the cable into the cable installation tool as shown.




16. Insert the cable installation tool into the BOTTOM end of the "B" section as shown.



17. Repeat the process performed in steps 11 and 12: Insert the crimped end of the cable up into the end of the sheave pocket at the end nearest the end of the "B" section as traced by the dotted arrows. With a motion like that of tightening a screw driver, twist the installation tool while holding the copper crimped end of the cable up into the sheave pocket. The cable will pop loose from the tool and up through the sheave pocket. Pull the crimped end out completely to remove the slack.


## ⚠ WARNING ⚠

The cable **MUST** pass down through the slot and out the bottom, then loop back in from the bottom of the "B" to feed through the sheave pocket exactly as shown in steps 14 - 17 in order to function properly. Failure to install the cable correctly as shown can cause wearing of the cable for which it is not designed which can result in failure of the cable. Failure of the cable while the lift is raised will result in a sudden and rapid lowering of the lift and the load possibly resulting in serious property damage, serious bodily injury, and/or death.



18. At this point your telescoping sections with the cable correctly installed should look like the pieces shown above.


**??Questions??** - Call Telpro Inc. Customer Service at 1-800-448-0822 or 701-775-0551



19. A correctly strung cable is shown above : Through the "A" section anchoring "V" from the bottom (a), into the top of the "B" section (b), back out through the sheave pocket at the end nearest the top of the telescoping section (c), into the slot of the "B" section (d), and out a final time through the end of the sheave pocket nearest the bottom of the "B" section (e).


## ⚠ WARNING ⚠

- **DO NOT** feed the cable through the areas marked "X" in the photo at left. Doing so will cause wearing on the cable for which it was not designed which can result in failure of the cable. Failure of the cable while the lift is raised will result in a sudden and rapid lowering of the lift and load possibly resulting in serious property damage, serious bodily injury, and/ or death.
- Failure to install the cable correctly as shown in these instructions can cause wearing of the cable for which it is not designed which can result in failure of the cable. Failure of the cable while the lift is raised will result in a sudden and rapid lowering of the lift and the load possibly resulting in serious property damage, serious bodily injury, and/or death.




20. Pull the slack out of the cable and slide the "A" section into the "B" section. In the case of the extension 186-00, slide the "E" section into the "F" section.

**??Questions??** - Call Telpro Inc. Customer Service at 1-800-448-0822 or 701-775-0551




21. Feed the copper crimped end of the cable through the frame sheave pocket from the top as shown.




22. MAKE SURE that the cable feeds over the TOP of the brass sheave as shown in steps 21 and 22.

## ⚠ WARNING ⚠

The cable **MUST** feed down from the top of the frame housing and over the top of the sheave exactly as shown in steps 21 - 22 in order to function properly. Failure to install the cable correctly as shown can cause wearing of the cable for which it is not designed which can result in failure of the cable. Failure of the cable while the lift is raised will result in a sudden and rapid lowering of the lift and the load possibly resulting in serious property damage, serious bodily injury, and/or death.




**DO NOT** feed the cable under the brass sheave on the frame as shown in this photo!




23. Pull the slack cable through the sheave pocket and slide the telescoping sections into the frame housing. As the telescoping sections lower into the frame, the slack cable will be drawn back up over the sheave.


# Summary Diagram:



24. Feed the copper crimped end of the cable through the winch drum and secure it behind the mooring tab by hand pulling the cable snug as shown.



25. Rotate the winch in the direction shown to take the slack out of the cable.



**??Questions??** - Call Telpro Inc. Customer Service at 1-800-448-0822 or 701-775-0551

## ASME Standards for wire rope (cable) inspection and replacement

Reprinted with permission from ASME B30.19-1993 Cableways

The following is intended as a helpful guide to the general topic of inspection and replacement of wire rope (cable). It is not intended to be an exhaustive treatment of the topic. **Frequent inspection (at least daily) and prompt replacement of any cable that shows any sign of wear is the responsibility of the owner and operator of the PANELLIFT® drywall lift.** With reference to the chart below at 19-2.4.3(b)(6) the PANELLIFT® cable is a nominal 1/8" high tensile aircraft cable (rope).

### 19-2.4.2 Inspection

#### (a) Frequent Inspection

(1) All running ropes in service should be visually inspected once each working day. A visual inspection shall consist of observation of all rope that can reasonably be expected to be in use during the day's operations. These visual observations should be concerned with discovering gross damage that may be an immediate hazard, such as listed below:

(a) distortion of the rope such as kinking, crushing, unstranding, birdcaging, main strand displacement, or core protrusion. Loss of rope diameter in a short rope length or unevenness of outer strands should provide evidence that the rope or ropes are to be replaced.

(b) general corrosion;

(c) broken or cut strands;

(d) number, distribution, and type of visible broken wires [see p. 19-2.4.3(b)(1), (2), and (7) for further guidance];

(e) core failure in rotation-resistant ropes; when damage is suspected, the rope shall either be removed from service or given an inspection as detailed in pare. 19-2.4.2(b).

(2) Care shall be taken when inspecting sections of rapid deterioration, such as flange points, crossover points, and repetitive pickup points on drums.

(3) Care shall be taken when inspecting certain ropes, such as rotation-resistant ropes, because of their higher susceptibility to damage and increased deterioration when working on equipment with limited design parameters. The internal deterioration of rotation-resistant ropes may not be readily observable.

#### (b) Periodic Inspection

(1) The inspection frequency shall be determined by a qualified person and shall be based on such factors as expected rope life (determined by experience on the particular installation or similar installations), severity of environment, percentage of capacity lifts, frequency rates of operation, and exposure to shock loads. Inspections need not be at equal calendar intervals and should be more frequent as the rope approaches the end of its useful life. The inspection shall be made at least every 1000 hr of cableway operation or annually, whichever comes first.

(2) Periodic inspections shall be performed by an appointed or authorized person. This inspection shall cover the entire length of rope. Only the surface wires of the rope need be inspected. No attempt should be made to open the rope. Any deterioration resulting in appreciable loss of original strength, such as described below, shall be noted, and a determination shall be made as to whether further use of the rope would constitute a hazard:

(a) points listed in pare. 19-2.4.2(a);

(b) reduction of rope diameter below nominal diameter due to loss of core support, corrosion, or wear of outside wires;

(c) severely corroded or broken wires at end connections;

(d) severely corroded, cracked, bent, worn, or improperly applied end connections.

(3) Care shall be taken when inspecting sections of rapid deterioration, such as the following:

(a) sections in contact with saddles, equalizer sheaves, or other sheaves, including track cable sheaves, where rope travel is limited;

(b) sections of the rope at or near terminal ends where corroded or broken wires may develop.

### 19-2.4.3 Rope Replacement

(b) Conditions such as the following shall be reason for questioning continued use of the rope or increasing the frequency of inspection.

(1) In running ropes, six randomly distributed broken wires in one lay, or three broken wires in one strand in one lay.

(2) One outer wire, broken at the contact point with the core of the rope, that has worked its way out of the rope structure and protrudes and loops out from the rope structure. Additional inspection of this section is required.

(3) Wear of one-third the original diameter of outside individual wires.

(4) Kinking, crushing, birdcaging, or any other damage resulting in distortion of the rope structure.

(5) Evidence of heat damage from any cause.

(6) Reductions from nominal diameter greater than those shown below:


Rope Diam. _____	Max. Allowable Reduction From Nominal Diam. _____
Up to 5/16 in. (8 mm)	1/64 in. (0.4 mm)
Over 3/8 in. up to 1/2 in. (13 mm)	1/32 in. (0.8 mm)
Over 9/16 in. up to 3/4 in. (19 mm)	3/64 in. (1.2 mm)
Over 7/8 in. up to 1 1/8 in. (29 mm)	1/16 in. (1.6 mm)
Over 1 1/4 in. up to 1 1/2 in. (38 mm)	3/32 in. (2.4 mm)

(7) In standing ropes, more than two broken wires in one lay in sections beyond end connections, or more than one broken wire at an end connection.


(c) Replacement rope shall have a nominal strength rating at least equal to the original rope furnished or recommended by the cableway manufacturer or designer, or a qualified person. Any deviation from the original size, grade, or construction shall be specified by the rope manufacturer, the cableway manufacturer or designer, or a qualified person.

(d) Ropes Not in Regular Use. All rope that has been idle for a period of a month or more due to shutdown or storage of a cableway on which it is installed shall be given an inspection in accordance with pare. 19-2.4.2(b) before it is placed in service. This inspection shall be for all types of deterioration and shall be performed by an appointed or authorized person.


# PARTS INDEX




# PARTS INDEX




Winch components




Mounting head components



Cross arm components



The special extension unit (186-00)



## CRADLE UNIT

Key	Part	Description
1	1-00	Complete cradle assembly
2	1-01	Cradle body
3	1-02	Pull pin with fasteners
4	1-03	Complete cross arm assembly
5	1-04	Cross arm body
6	1-05	Support hook with fasteners
7	1-06	End cap
8	1-07	Outrigger with end cap
9	1-17	Complete mounting head assembly
10	1-18	Complete spring yoke pin assembly

## FRAME UNIT

Key	Part	Description
15	2-00	Complete frame assembly with winch and standard "A" and "B" sections
16	2-01	Frame housing
17	2-02	Winch post with pin and fastener
18	2-03	Slide bar with pins
19	2-04	Slide bar lock with fasteners
20	2-05	Cable 13.5' 1/8" aircraft
21	2-06	Brass sheave with axle and pins
22	2-07	Retaining hook
23	2-08	4' "A" section (inner)
24	2-09	4' "B" section with sheaves

## WINCH UNIT

Key	Part	Description
	3-00	Complete winch assembly
25	3-01	Winch wheel with bronze flange bearings
26	3-03	7/8" bushing
28	3-04	1/2" bolt with washer and nut
29	3-05	Complete brake arm assembly
30	3-07	Tension spring "B"
32	3-08	Brake handle cover
33	3-09	Brake hub with bolts
34	3-10	Red handle

## TRIPOD BASE UNIT

Key	Part	Description
	4-00	Complete tripod base assembly
36	4-01	Center leg
37	4-02	Tension spring "S"
38	4-03	Backstop tip
39	4-04	Tie arm with fasteners
40	4-05	Outer leg with fasteners
41	4-06	Caster 5"

## SPECIAL 186-00 EXTENSION UNIT FOR CEILINGS OR WALLS UP TO 15'

Key	Part	Description
	186-00	Complete extension unit
43	186-01	6' "E" section (inner)
44	186-02	6' "F" section with sheaves
45	186-03	Cable 17 1/3' 1/8" aircraft
46	186-04	Brass sheave with axle and pins

# RECOMMENDATIONS & SPECIAL INFORMATION

---

## IMPORTANT

- As with any lifting equipment, **ALWAYS WEAR A HARD HAT** when operating unit.
- **DO NOT ATTEMPT TO USE THE PANELLIFT® DRYWALL LIFT IF ANY PART IS MISSING, DAMAGED, OR WORN. ORDER A REPLACEMENT PART IMMEDIATELY!**
- The load rating of the PANELLIFT® Drywall Lift is 150 lbs. **DO NOT** load the unit beyond this limit. **DO NOT** load more than one sheet of drywall at a time on the PANELLIFT® Drywall Lift.
- Moving the PANELLIFT® Drywall Lift from a cold environment to a warm one may cause condensation to form on metal surfaces creating a potential for malfunction: **Allow the unit to reach working room temperature and check to make sure that the winch brake drum is clean and dry before operating.**
- The PANELLIFT® Drywall Lift is designed **EXCLUSIVELY** for use as a **DRYWALL LIFT** and is intended to be used for **NO OTHER PURPOSE.**

1. Inspect cable **FREQUENTLY** (At least daily and before each use). Replace when worn.
2. Occasionally oil the cable sheaves and caster bearings.
3. Store the PANELLIFT® Drywall Lift in a dry place.
4. Do not allow grease or oil to contact the surface of the winch brake drum. (Powered gypsum applied to the brake will help dry the surface.
5. Apply household paraffin to the surfaces of the telescoping sections, for smoother action.
6. Take reasonable care to avoid damaging the PANELLIFT® Drywall Lift when transporting it.