

# PLB 29 DI ROCK DRILL



## PICK THE RIGHT ROCK DRILL!

**The PLB 29 DI ROCK DRILL is a proven performer in Mining and Construction. Top drilling power. Long working life. Minimum wear. Smooth running. Easy to service.**

**One of the worlds's best!**



**PLB 29 DI Rockdrill linked to a DT 180 Airleg.**

## Technical Data PLB 29 DI

<b>WEIGHT</b>	29 kg
<b>LENGTH</b>	690 mm
<b>PISTON DIA</b>	90 mm
<b>PISTON STROKE</b>	65 mm
<b>AIR CONSUMPTION</b>	5.3 m <sup>3</sup> /min at 6 bar
<b>AIR CONNECTION</b>	32 mm/1¼"
<b>AIR OPERATING PRESSURE</b>	5—6 Bar
<b>WATER CONNECTION</b>	20 mm/¾"
<b>FLUSHING WATER</b>	8.8 Litres/min
	MINIMUM FOR 2.4 m DRILL AT 0.5 BAR LOWER THAN OPERATING PRESSURE STANDARD WATER TUBE 3 mm
<b>TOOL SHANK</b>	22 mm x 108 mm / 7/8" x 4¼"
<b>OPTIONS</b>	TOOL SHANK 25 mm x 108 mm / 1" x 4¼" WATER TUBE 4 mm DIAMETER RIGHT HAND ROTATION IN MODEL PLB 24DI
<b>RECOMMENDED AIRLEGS</b>	DT 100 short length, double telescope, 1100 mm retracted, 1040 mm stroke DT 180 Standard length, double telescope, 1505 mm retracted, 1840 mm stroke DT 200 Extended length, double telescope, 1645 mm retracted, 2100 mm stroke ST 052 Short length, single telescope, 910 mm retracted, 525 mm stroke ST 135 Standard length, single telescope, 1920 mm retracted, 1350 mm stroke

AUSTRALIAN SALES AND SERVICE

**SWISS INDUSTRIAL COMPANY (AUST) PTY LTD**



**SYDNEY** (02) 674 2122

**PERTH** (09) 362 4911

**KALGOORLIE** (090) 21 4400

**MT ISA** (077) 43 8111

**BROKEN HILL** (080) 884 644